







4G LTE USB Modem

Introducing the 4G LTE Ovation™ MC679, the market's slimmest and most compact 4G LTE USB modem. The MC679 is the next generation of the Novatel Wireless Ovation USB mobile broadband modem portfolio, building on award-winning innovation and design, proven performance and industry-eading flexibility, convenience and reliability. Experience life in the fast lane with blazing fast 4G LTE mobile broadband.

Slim, Durable and Compact Design

Perfect for the frequent traveler! The MC679 is the market's slimmest and most compact 4G LTE USB modem currently available for North America. Its hinged USB connector provides flexible orientation, ease of use and can simply fold closed for additional protection in transport.

Internal Advanced Antenna with MIMO

Connectivity when you need it the most. The tri-band advanced antenna includes MIMO with receive diversity, providing optimal performance when you need it most. The compact internal antenna is designed without fragile external pieces. The device itself extends only an inch out of your notebook.

Versatility and Compatibility

The perfect solution. The MC679 is backward-compatible to high-speed DC HSPA+ and HSPA+ networks. The MC679 device also comes complete with MobiLink™ Connection Manager software for a quick setup. Compatible on both Windows® and Mac® operating systems, it is the perfect solution to get up and running quickly and easily.









4G LTE USB Modem

GPS frequency 1575 MHz band

Technology/Bands

- Technology: LTE/DC HSPA+/HSPA+/GPRS/EDGE
- Band Designation:
 LTE AWS/700 MHz bands (with receive MiMo)
 DC HSPA+/HSPA+ 850/1900/2100 MHz (with RX diversity)
 Quad-band GPRS/EDGE 850/900/1800/1900 MHz

Data Speeds

- LTE Up to 50 Mbps upload (theoretical value)
- LTE Up to 100 Mbps download (theoretical value)

Dimensions and Weight

- 88 mm x 35 mm x 12 mm (3.46" x 1.38" x 0.47")
- 35 g (1.23 oz)

Form Factor

- USB with hinge connector
- USIM card slot

Visual Indicator (LED)

 Multi-color LED indicator for real-time service status, technology modes and error conditions

Environmental

- Operating temperature: 0°C to 40°C (32°F to 104°F)
- Storage temperature: -20°C to 65°C (-4°F to 149°F)

Connectivity Features

Auto install

Operating Systems Supported

- Windows® 7, Vista, XP
- Mac OS® X 10.4 or higher
- Linux®

System Requirements

- Type A USB Port
- Internet browser
- Hard Disk Space: 100 MB
- Memory: 128 MB

Standards/Approvals/Certifications

- FCC and Industry Canada
- PTCRB
- GCF
- Microsoft® WHQL
- RoHS / WEEE Compliant

Software and Applications

- MobiLink Connection Manager
- Plug & Play
- Internet, Intranet, Email, Connection log
- SMS

Standard Package Contents

- Ovation MC679 USB Modem
- Quick Start Guide



For More Information: e-mail: sales@nvtl.com

NASDAQ: NVTL www.novatelwireless.com

