


# Product Description



HUAWEI E589u-512 Mobile WiFi  
V100R001

**Issue** 01  
**Date** 2012-05-18

HUAWEI TECHNOLOGIES CO., LTD.





Huawei Technologies Co., Ltd. provides customers with comprehensive technical support and service. Please feel free to contact our local office or company headquarters.

## Huawei Technologies Co., Ltd.

Address: Huawei Industrial Base  
Bantian, Longgang  
Shenzhen 518129  
People's Republic of China

Website: <http://www.huawei.com>

Email: [mobile@huawei.com](mailto:mobile@huawei.com)

**Copyright © Huawei Technologies Co., Ltd. 2012. All rights reserved.**

No part of this document may be reproduced or transmitted in any form or by any means without prior written consent of Huawei Technologies Co., Ltd.

### Trademarks and Permissions



**HUAWEI** and other Huawei trademarks are trademarks of Huawei Technologies Co., Ltd.

All other trademarks and trade names mentioned in this document are the property of their respective holders.

### Notice

The information in this document is subject to change without notice. Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute the warranty of any kind, express or implied.

---

# About This Document

---

## Purpose and Organization

This document describes the major functions, services, and system architecture of HUAWEI E589u-512 Mobile WiFi (E589u-512 for short).

The following table lists the content of each chapter.

Chapter	Describes
1 Overview	Network modes, major functions and services, and appearance.
2 Features	Features and technical specifications.
3 Services and Applications	Services and applications.
4 System Architecture	System architecture.
5 Packing List	Items contained in the product package.



## Change History

Issue	Details	Date
01	Released the first version.	2012-05-18



# Contents

---

<b>1 Overview</b> .....	<b>6</b>
<b>2 Features</b> .....	<b>8</b>
2.1 Main Features .....	8
2.2 Technical Specifications.....	9
2.2.1 Hardware .....	9
2.2.2 Software .....	11
<b>3 Services and Applications</b> .....	<b>13</b>
3.1 Data Service .....	13
3.2 SMS.....	13
<b>4 System Architecture</b> .....	<b>14</b>
4.1 System Architecture .....	14
4.2 Functional Modules .....	15
<b>5 Packing List</b> .....	<b>16</b>

# 1 Overview

---

The E589u-512 is a multimode terminal for high-speed wireless network access. It supports multiple network modes and is specially designed for small office/home office (SOHO) users and business professionals.

The E589u-512 supports the following frequency bands:

- LTE 2600/AWS/1900 MHz
- DC-HSPA+/HSPA+/HSPA/UMTS 1900/850 MHz
- EDGE/GPRS/GSM 850/900/1800/1900 MHz

The E589u-512 supports the following network modes:

- Long Term Evolution (LTE)
- Dual Carrier High Speed Packet Access Plus (DC-HSPA+)
- High Speed Packet Access Plus (HSPA+)
- High Speed Uplink Packet Access (HSUPA)
- High Speed Downlink Packet Access (HSDPA)
- Universal Mobile Telecommunications System (UMTS)
- Enhanced Data rates for GSM Evolution (EDGE)
- General packet radio service (GPRS)
- Global System for Mobile Communications (GSM)

The E589u-512 provides the following services:

- High-speed LTE packet data service of up to 100 Mbit/s
- High-speed DC-HSPA+ packet data service of up to 43.2 Mbit/s
- High-speed HSPA+ packet data service of up to 21.6 Mbit/s
- High-speed HSPA (HSUPA/HSDPA)/UMTS packet data service of up to 14.4 Mbit/s
- EDGE/GPRS packet data service of up to 236.8 kbit/s
- UMTS/GSM Short Message Service (SMS)

The E589u-512 can be connected to multiple wireless devices using the Wireless Fidelity (Wi-Fi), allowing users to access the Internet, and send/receive SMS and email messages when in the coverage areas of LTE, DC-HSPA+, HSPA+, HSPA, UMTS, EDGE, GPRS, or GSM networks. With high-speed network access, reliable performance, and easy-to-operate user interface (UI), the E589u-512 provides users

with better wireless network access experience and operators with substantially increased average revenue per user (ARPU).

Figure 1-1 shows the E589u-512.

**Figure 1-1** E589u-512



# 2 Features

## 2.1 Main Features

The E589u-512 supports the following features:

- Downlink LTE packet data service of up to 100 Mbit/s
- Uplink LTE packet data service of up to 50 Mbit/s
- Downlink LTE -> Wi-Fi packet data service of up to 35 Mbit/s
- Downlink DC-HSPA+ packet data service of up to 43.2 Mbit/s
- Downlink HSPA+ packet data service of up to 21.6 Mbit/s
- Downlink HSDPA packet data service of up to 14.4 Mbit/s
- Uplink DC-HSPA+/ HSPA+/HSUPA packet data service of up to 5.76 Mbit/s
- Uplink and downlink UMTS packet data service of up to 384 kbit/s
- Uplink and downlink EDGE packet data service of up to 236.8 kbit/s
- Uplink and downlink GPRS packet data service of up to 85.6 kbit/s
- Packet switched (PS) domain data service based on LTE, UMTS and GSM
- SMS based on UMTS and GSM
- Wi-Fi and Wi-Fi Protected Setup (WPS)
- Concurrent wireless connections from 10 users
- Built-in Dynamic Host Configuration Protocol (DHCP) server, Domain Name System (DNS) relay, and network address translation (NAT)
- 3000 mAh built-in battery (non-removable) that supports up to 10 hours operating time
- Maximum standby time is 360 hours while Wi-Fi is off
- Universal Serial Bus (USB) extension cable for convenient connection in various usage scenarios
- Thin film transistor liquid crystal display (TFT-LCD)
- Standard micro-USB port
- Built-in LTE, UMTS, and wireless local area network (WLAN) antennas
- Micro Secure Digital (microSD) memory card
- Windows XP, Windows Vista, Windows 7, and Mac OS X 10.5, 10.6, and 10.7



## 2.2 Technical Specifications

### 2.2.1 Hardware

Table 2-1 lists the E589u-512's hardware specifications.

**Table 2-1** Hardware specifications

Item	Specifications	
Standards compliance	WAN: LTE/DC-HSPA+/HSPA+/HSPA/UMTS/EDGE/GPRS/GSM	
	WLAN: IEEE 802.11b/g/n	
Operating frequency	LTE: 2600/AWS/1900 MHz	
	DC-HSPA+/HSPA+/HSPA/UMTS: 1900/850 MHz	
	EDGE/GPRS/GSM: 1900/1800/900/850 MHz	
	WLAN: 2400–2483 MHz	
Memory	128 MB NAND flash and 64 MB SRAM	
Maximum transmit power	LTE: 22 dBm	
	UMTS: 23 dBm	
	WLAN	802.11b: 13 dBm
		802.11g: 11 dBm
802.11n: 11 dBm		
Receiver sensitivity	LTE	2100 MHz: -97 dBm@10 MHz
		1800 MHz: -94 dBm@10 MHz
		2600 MHz: -95 dBm@10 MHz
		900 MHz: -94 dBm@10 MHz
		DD800MHz: -94 dBm@10 MHz
	UMTS : -109 dBm@3.8 MHz	
	WLAN 802.11b: -76 dBm@11 Mbit/s or -82 dBm@1 Mbit/s	
	WLAN 802.11g: -65 dBm@54 Mbit/s	
	WLAN 802.11n: -64 dBm@65 Mbit/s	
	WLAN rate	802.11b: up to 11 Mbit/s
802.11g: up to 54 Mbit/s		
802.11n: support for MCS0–MCS7; up to 72.2 Mbit/s		

Item	Specifications
Maximum power consumption	4.3 W
Power supply	AC: 100–240 V
	DC: 5 V, 2 A
Battery	Type: Li-ion battery (rechargeable and non-removable)
	Capacity: 3.7 V, 3000 mAh
	Maximum operating time: 10 hours
	Maximum standby time: 360 hours while Wi-Fi is off
External interfaces	Micro-USB port
	Standard microSD card interface
	Standard 6-pin SIM card interface
	External main antenna interface
Display	TFT-LCD
Keys	Wi-Fi/Power multiplexing key, WPS switch, and Reset key
Antenna	Built-in LTE/UMTS/GSM main antenna
	Built-in LTE/UMTS diversity antenna
	Built-in WLAN antenna
	External LTE/UMTS/GSM main antenna interface
Dimensions (H x W x D)	13.5 mm x 62 mm x 113 mm
Weight	About 140 g
Ambient temperature	Operating: 0°C to +35°C
	Storage: –20°C to +70°C
Humidity	5% to 95% (non-condensing)
<b>Note</b> SRAM = static random-access memory WAN = wide area network	

## 2.2.2 Software

Table 2-2 lists the E589u-512's software specifications.

**Table 2-2** Software specifications

Item	Description
SMS	<ul style="list-style-type: none"> <li>• Write, send, and receive messages.</li> <li>• Set SMS center number.</li> <li>• Save up to 300 messages to local storage.</li> <li>• Choose to save messages to local storage (default storage location) or SIM card.</li> <li>• Notify users of new messages.</li> </ul>
Network connection setup	<ul style="list-style-type: none"> <li>• Create, delete, and edit APNs.</li> <li>• Set up dial-up connection automatically.</li> </ul>
WLAN setup	<ul style="list-style-type: none"> <li>• Set the SSID.</li> <li>• Broadcast and hide the SSID.</li> <li>• Open system and shared key authentication.</li> <li>• ASCII and HEX keys.</li> <li>• 64/128-bit WEP encryption.</li> <li>• 256-bit WPA-PSK and WPA2-PSK encryption.</li> <li>• TKIP and AES encryption algorithm.</li> <li>• Automatic rate adjustment.</li> <li>• Station management.</li> <li>• Turn off Wi-Fi at a specified time.</li> </ul>
Firewall setup	<ul style="list-style-type: none"> <li>• Enable/Disable the firewall.</li> <li>• LAN IP filter.</li> <li>• Port forwarding.</li> <li>• Virtual server.</li> <li>• DMZ service.</li> </ul>
DHCP setup	<ul style="list-style-type: none"> <li>• Enable/Disable DHCP server.</li> <li>• Set up address pool on the DHCP server.</li> <li>• Set the DHCP lease time.</li> </ul>
System requirements	<ul style="list-style-type: none"> <li>• Windows XP, Windows Vista, and Windows 7.</li> <li>• Mac OS X 10.5, 10.6, and 10.7.</li> <li>• The computer's hardware must meet or exceed the recommended configuration for the operating system running on the computer.</li> <li>• Display resolution: 1024 x 768 pixels or higher.</li> </ul>

Item	Description
Others	Network connection: <ul style="list-style-type: none"><li>• Automatic network selection and registration</li><li>• Manual network selection and registration</li></ul>
	Network status display: signal strength, operator name, system mode, and others.
	Optional network connection types, for example: <ul style="list-style-type: none"><li>• LTE preferred</li><li>• 3G preferred</li><li>• 2G preferred</li></ul>
	PIN management: <ul style="list-style-type: none"><li>• Edit</li><li>• Enable/Disable</li><li>• Verify</li></ul>
<b>Note</b> 3G = 3rd generation AES = Advanced Encryption Standard APN = Access Point Name ASCII = American Standard Code for Information Interchange DMZ = demilitarized zone HEX = hexadecimal LAN = local area network PIN = personal identification number SSID= service set identifier TKIP = Temporary Key Integrity Protocol WEP = Wired Equivalent Privacy WPA-PSK = Wi-Fi Protected Access Pre-Shared Key	


# 3 Services and Applications

## 3.1 Data Service

The E589u-512 can be used as a wireless modem when Wi-Fi is enabled. Users can set up wireless connections between Wi-Fi enabled user equipment and the E589u-512, and then access the Internet.

A maximum of 10 users can use Wi-Fi enabled devices to access the E589u-512 simultaneously, which sets up a WLAN.

**Figure 3-1** Access from multiple devices using Wi-Fi



## 3.2 SMS


The E589u-512 allows users to write, send, and receive messages. The E589u-512's web interface provides powerful message management functions, such as management of received, sent and draft messages.

# 4 System Architecture

## 4.1 System Architecture

Figure 4-1 shows the E589u-512's system architecture.

Figure 4-1 System architecture



## 4.2 Functional Modules

1. **Radio Frequency Module:** It sends/receives radio signals and modulates/demodulates the radio frequency (RF) signals and baseband signals.
2. **Baseband Signal Processing:** It processes LTE/DC-HSPA+/HSPA+/HSPA/UMTS/EDGE/GPRS/GSM baseband digital signals, including:
  - Modulating/Demodulating LTE baseband signals.
  - Modulating/Demodulating DC-HSPA+/HSPA+/HSPA/UMTS baseband signals.
  - Modulating/Demodulating EDGE/GPRS/GSM baseband signals
  - Encoding/Decoding the LTE channel.
  - Encoding/Decoding DC-HSPA+/HSPA+/HSPA/UMTS channel.
  - Encoding/Decoding EDGE/GPRS/GSM channel.
3. **Bottom Layer Driver:** It drives peripherals, including USB device, Wi-Fi device, screen, button, SIM card and microSD card.
4. **Protocol Stack System:** It processes protocols of LTE/DC-HSPA+/HSPA+/HSPA/UMTS/EDGE/GPRS/GSM and TCP/IP.
5. **Application System:** It provides management system, including SMS, PS domain service, Wi-Fi configuration, network service, WEB service and WEB page. The user can set management parameters by WEB page.
6. **User Interface:** It provides human-computer interaction, including screen and button.

# 5 Packing List

Table 5-1 lists the items contained in the package of the E589u-512.

**Table 5-1** Packing list of the E589u-512

Item	Quantity	Remarks
Mobile WiFi (including non-removable battery)	1	Standard
USB cable	1	Standard
Power adapter	1	Standard
Quick Start	1	Standard
Safety Information	1	Standard
Warranty Card	1	Optional



# A Acronyms and Abbreviations

---

<b>3G</b>	3rd generation
<b>3GPP</b>	3rd Generation Partnership Project
<b>AES</b>	Advanced Encryption Standard
<b>APN</b>	Access Point Name
<b>ARP</b>	Address Resolution Protocol
<b>ARPU</b>	average revenue per user
<b>ASCII</b>	American Standard Code for Information Interchange
<b>BSS</b>	Base Station System
<b>CS domain</b>	circuit switched domain
<b>DC-HSPA+</b>	Dual Carrier High Speed Packet Access Plus
<b>DHCP</b>	Dynamic Host Configuration Protocol
<b>DL</b>	Data Link
<b>DMZ</b>	demilitarized zone
<b>DNS</b>	Domain Name System
<b>EDGE</b>	Enhanced Data rates for GSM Evolution
<b>GERAN</b>	GSM/EDGE Radio Access Network
<b>GPRS</b>	General packet radio service
<b>GSM</b>	Global System for Mobile Communications
<b>HEX</b>	hexadecimal
<b>HSUPA</b>	High Speed Uplink Packet Access
<b>HSDPA</b>	High Speed Downlink Packet Access
<b>HSPA+</b>	High Speed Packet Access Plus
<b>HTTP</b>	Hypertext Transfer Protocol

<b>IC</b>	Integrated Circuit
<b>ICMP</b>	Internet Control Message Protocol
<b>IP</b>	Internet Protocol
<b>LAN</b>	local area network
<b>LTE</b>	Long Term Evolution
<b>MAC</b>	Medium Access Control
<b>MexE</b>	Mobile Execution Environment
<b>microSD card</b>	micro Secure Digital card
<b>MS</b>	Mobile Station
<b>NAS</b>	Non-Access Stratum
<b>NAT</b>	network address translation
<b>OS</b>	Operating System
<b>PDCP</b>	Packet Data Convergence Protocol
<b>PIN</b>	personal identification number
<b>PPP</b>	Point-to-Point Protocol
<b>PS domain</b>	packet switched domain
<b>RF</b>	radio frequency
<b>RLC</b>	Radio Link Control
<b>RRC</b>	Radio Resource Control
<b>SGSN</b>	Serving GPRS Support Node
<b>SIM</b>	Subscriber Identity Module
<b>SMS</b>	Short Messaging Service
<b>SNDCP</b>	Subnetwork Dependent Convergence Protocol
<b>SOHO</b>	small office/home office
<b>SRAM</b>	static random-access memory
<b>SSID</b>	service set identifier
<b>TCP</b>	Transmission Control Protocol
<b>TFT-LCD</b>	thin film transistor liquid crystal display
<b>TKIP</b>	Temporary Key Integrity Protocol
<b>TR</b>	Technical Report
<b>TS</b>	Technical Specification
<b>UDP</b>	User Datagram Protocol
<b>UE</b>	User Equipment

<b>UMTS</b>	Universal Mobile Telecommunications System
<b>USAT</b>	USIM Application Toolkit
<b>USB</b>	Universal Serial Bus
<b>USIM</b>	UMTS Subscriber Identity Module
<b>UTRAN</b>	UMTS Terrestrial Radio Access Network
<b>WAN</b>	wide area network
<b>WEP</b>	Wired Equivalent Privacy
<b>Wi-Fi</b>	Wireless Fidelity
<b>WLAN</b>	wireless local area network
<b>WPA-PSK</b>	Wi-Fi Protected Access Pre-Shared Key
<b>WPS</b>	Wi-Fi Protected Setup